



		FRIMÅLTOLERANCER DS 2075 - DIN 7168														
		For mål uden toleranceangivelser gælder den afkrydsede række														
		linære	over	0	6	30	120	315	1000	2000	korteste ben					
		mål	til	6	30	120	315	1000	2000	4000	vinkel	over	0	10	50	120
		middel	+/-	.1	.2	.3	.5	.8	1.2	2.0	mål	til	10	50	120	.
		grov	+/-	.2	.5	.8	1.2	2.0	3.0	4.0	middel	+/-	1°	30	20	10
		m. grov	+/-	.5	1.0	1.5	2.0	3.0	4.0	6.0	m. grov	+/-	1°	2°	1°	30
DATO	SIGN.	RETTELSE	UBEN. REJFN.:		SCANDINAVIAN STEELHOUSE							MÅLF:	TEGN.	25-Jan-12	MOK	
EMNEVEGT(Kg):			UBEN. OVERFL.:		WWW.BALKON.DK							1:50	GODK.	25-Jan-12	JL J	
MAT. VARENR.:			UBEN. RADIER:									REVISION NR.:			1.0+	
MAT. DIMENSION:			UBEN. SVEJSN:		Steelhouse carporten											
MAT. KVALITET:					1950x3770, H=2000/2500										703689	
OVERFL. BEH.: Hot galvanize																