



10 mm termotag i opal

		FRIMÅLTOLERANCER DS 2075 - DIN 7168															
		For mål uden toleranceangivelser gælder den afkrydsede række															
										korteste ben							
		linjre mål	over til	0	6	30	120	315	1000	2000	4000	vinkel mål	over til	0	10	50	120
		middel	+/-	.1	.2	.3	.5	.8	1.2	2.0	4.0	middel	+/-	1°	2°	3°	10°
		grov	+/-	.2	.5	.8	1.2	2.0	3.0	4.0	6.0	m. grov	+/-	1°	2°	3°	30°
		m. grov	+/-	.5	1.0	1.5	2.0	3.0	4.0	6.0							
DATO	SIGN.	RETTELSE	UBEN. REJFN.:														
EMNEVEGT(kg):			UBEN. OVERFL.:		SCANDINAVIAN STEELHOUSE												
MAT. VARENR.:			UBEN. RADIER:		WWW.BALKON.DK												
MAT. DIMENSION:			UBEN. SVEJSN:		MÅLF: TEGN. 28-Maj-15 MBN												
MAT. KVALITET:					I: 10 GODK. 28-Maj-15 JL J												
OVERFL. BEH.:	Hot galvanize		3000x1000, H=250		REVISION NR.: 1.2+												
776024																	