



10 mm termotag i opal

		FRIMÅLTOLERANCER DS 2075 - DIN 7168														
		For mål uden toleranceangivelser gælder den afkrydsede række														
		linære	over	0	6	30	120	315	1000	2000	korteste ben					
		mål	til	6	30	120	315	1000	2000	4000	vinkel	over	0	10	50	120
		middel	+/-	.1	.2	.3	.5	.8	1.2	2.0	mål	til	10	30	20	10
		grov	+/-	.2	.5	.8	1.2	2.0	3.0	4.0	middel	+/-	1°	30	20	10
		m. grov	+/-	.5	1.0	1.5	2.0	3.0	4.0	6.0	m. grov	+/-	1°	2°	1°	30
DATO	SIGN.	RETTELSE	UBEN. REJFN.:	SCANDINAVIAN STEELHOUSE								MÅLF:	TEGN.	28-Maj-15	MBN	
EMNEVEGT(Kg):	UBEN. OVERFL.:			WWW.BALKON.DK								2:25	GODK.	28-Maj-15	JL J	
MAT. VARENR.:	UBEN. RADIER:											REVISION NR.: 1.1+				
MAT. DIMENSION:	UBEN. SVEJSN:			Buet Steelhouse Baldakin								776030				
MAT. KVALITET:				1455x1000, H=250												
OVERFL. BEH.:	Hot galvanize															