



		FRIMÅLSTOLERANCER DS 2075 - DIN 7168														
		For mål uden toleranceangivelser gælder den afkrydsede række														
		linære	over	0	6	30	120	315	1000	2000	korteste ben					
		mål	til	6	30	120	315	1000	2000	4000	vinkel	over	0	10	50	120
		middel	+/-	.1	.2	.3	.5	.8	1.2	2.0	mål	til	10	50	120	.
		grov	+/-	.2	.5	.8	1.2	2.0	3.0	4.0	middel	+/-	1°	30	20	10
		m. grov	+/-	.5	1.0	1.5	2.0	3.0	4.0	6.0	m. grov	+/-	1°	2°	1°	30
DATO	SIGN.	RETTELSE	UBEN. REJFN.:		UBEN. OVERFL.:		SCANDINAVIAN STEELHOUSE		MÅLF:		TEGN.	23-Mar-10	MOK			
EMNEVEGT(Kg):		UBEN. RADIER:		WWW.BALKON.DK		1:50		GODK.		23-Mar-10		JL J				
MAT. VARENR.:		UBEN. SVEJSN:		Steelhouse carporten		REVISION NR.:		1.4+								
MAT. DIMENSION:		6000x3600, H=2000/2500		703000												
MAT. KVALITET:																
OVERFL. BEH.: Hot galvanize																